

ADVANCE C2000

The ADVANCE UV Systems Pty Ltd, **ADVANCE C2000** ultra-violet water disinfection unit for disinfecting drinking or process water. This model can also be sized to disinfect treated waste water, and other liquids with low UV transmission.

Reactor: Stainless steel reactor, horizontal mounting with outlet pointing up.

Material	:	Stainless steel g316L, electropolished
In-outlet connection	:	2" male BSPT (3" Table E flange)
Reactor volume (litres)	:	8.7 l
Reactor length overall approx. (A)	:	1,315 mm
Space required for servicing (B)	:	1,300 mm
Reactor Weight dry (kg)	:	11.3 kg
Max. operating pressure (bar)	:	10 bar
Lamp power W	:	240 watts
UV-C output W	:	76 watts
Number of lamps (per unit)	:	1
Lamp life	:	12,000 hours
Peak flow (at Dose 25 mJ/cm ² , UVT 95%)	:	24.7 m ³ /h
Peak flow (at Dose 40 mJ/cm ² , UVT 95%)	:	16.8 m ³ /h

Features:

- Lamp parallel to water flow
- View/monitor port
- Easy to install mounting brackets

Power Supply Box: Fan cooled, ABS with standard 10A GPO plug

Input	:	220-240 VAC, 50-60 Hz, 1.6A
Power consumption W	:	270 watts
Max. ambient temperature (°C.)	:	40°C
Power box dimensions (mm)	:	380 x 280 x 130 mm
Power box weight (kg)	:	6 kg
Power box protection class	:	IP54
Lamp lead length (m)	:	2 m

Options: (additional cost)

- UV intensity monitor
- Higher IP rating
- Enclosure material 316ss, or glass reinforced polyester
- Longer lamp lead
- Different mains supply
- Chamber thermostat with solenoid valve for over-temperature protection

