

ADVANCE C50

The ADVANCE UV Systems Pty Ltd, **ADVANCE C50** ultra-violet water disinfection unit for disinfecting drinking or process water. This model can also be sized to disinfect treated waste water, and other liquids with low UV transmission.

Reactor: Stainless steel reactor, horizontal mounting with outlet pointing up.

Material	:	Stainless steel g316L, electropolished
In-outlet connection	:	$\frac{3}{4}$ " (1" option) male BSPT
Reactor volume (litres)	:	0.6 l
Reactor length overall approx. (A)	:	355 mm
Space required for servicing (B)	:	300 mm
Reactor Weight dry (kg)	:	0.9 kg
Max. operating pressure (bar)	:	10 bar
Lamp power W	:	12 watts
UV-C output W	:	3.6 watts
Number of lamps (per unit)	:	1
Lamp life	:	9000 hours
Peak flow (40 mJ/cm ² , UVT 95%)	:	458 lph
Peak flow (25 mJ/cm ² , UVT 95%)	:	734 lph

Features:

- Lamp parallel to water flow
- View/monitor port
- Easy to install movable mounting brackets

Options (additional cost)

- Sampling ports

Power Supply Box: Different versions available all with standard 10A GPO plug and 2m lamp lead.

Version: **PSL1B-040-BRK4**

Includes visible lamp operating (green) and lamp fault (red) LED indication. IP65

Dimensions: 105 x 60 x 30 mm, Weight: 0.4 kg

Version: **PSL1B-040-DDCV**

Includes visible and audible lamp fail alarm, lamp operation count down timer 365 – 0 days, lamp change alert, for indoor operation only.

Dimensions: 205 x 75 x 53 mm, Weight: 0.7 kg

Version: **PSL1B-040-A**

Includes power on indicator, visible and audible lamp fail alarm, hours run meter, IP65.

Dimensions: 300 x 300 x 150 mm, Weight: 5.5 kg

Options: (additional cost)

- UV intensity monitor
- Stainless steel enclosure or glass reinforced polyester enclosure
- Spare set of volt free contacts

